

Leica iCON gps 80

Increasing productivity

Maximising uptime

icon
intelligent construction

The Leica iCON gps 80 GNSS machine receiver takes machine control to the next level.

The iCON gps 80 GNSS receiver in combination with CGA60 GNSS antenna increases the performance of your iCON machine control solution, allowing you to work more productively than ever before.



Leica iCON gps 80
GNSS machine receiver



CGA60 GNSS antenna

Increase the uptime of your dozers, excavators, drilling and dredging machines, wheel loaders, graders and pavers. Profit from fast, reliable 3D positioning and highly productive operation by a perfectly tuned machine control system.

Customer benefits

- Improved sensor integration into the machine solution for even more automatic handling, ease-of-use and speed of work
- Increased performance and productivity – all parts of the system fit together seamlessly
- CAN-bus protocol specifically designed for GNSS machine control, provides robust and reliable communication, more uptime
- Flexible communication thanks to the built-in modem and removable radios
- xRTK allows machine guidance in difficult environments, increasing machine productivity
- Leica iCON telematics provides remote access to the machine computer for fast, perfect data transfer and support

Leica iCON gps 80

The most versatile, powerful GNSS machine receiver



All GNSS relevant information is available on the built-in display. No separate controller or device needed to configure the receiver.



Easy firmware update and data exchange via USB stick.



Flexible communication with built-in modem, slot-in radio or external radio. Easy switch between radio and modem usage.



Clearly labelled connectors for easy system installation.

Leica iCON gps 80 GNSS Machine Control Receiver

		Leica iCG81 Single GNSS Machine Entry	Leica iCG82 Dual GNSS Ready Entry	Leica iCG81 Single GNSS Machine Standard	Leica iCG81 Single GNSS Machine Ultimate	Leica iCG82 Dual GNSS Ready Standard	Leica iCG82 Dual GNSS Ready Ultimate	Leica iCG82 Dual GNSS Standard	Leica iCG82 Dual GNSS Ultimate
Supported GNSS Systems	GPS L2	•	•	✓	✓	✓	✓	✓	✓
	GLONASS	•	•	✓	✓	✓	✓	✓	✓
	GPS L5	•	•	•	✓	•	✓	•	✓
	Galileo	•	•	•	✓	•	✓	•	✓
	BeiDou	•	•	•	✓	•	✓	•	✓
RTK Performance	Low accuracy RTK (2/50)	•	•	•	•	•	•	•	•
	High accuracy RTK	•	•	✓	✓	✓	✓	✓	✓
	RTK up to 2.5 km	•	•	✓	✓	✓	✓	✓	✓
	RTK unlimited	•	•	✓	✓	✓	✓	✓	✓
	Network RTK	•	•	✓	✓	✓	✓	✓	✓
Positioning Update & Data Recording	2 Hz positioning	•	•	✓	✓	✓	✓	✓	✓
	20 Hz positioning	•	•	✓	✓	✓	✓	✓	✓
	Raw data RINEX logging	•	•	•	✓	•	✓	•	✓
Additional Features	RTK Reference Station functionality	•	•	•	✓	•	✓	•	✓
	NMEA out	•	•	•	✓	•	✓	•	✓
	Dual positioning and heading	-	•	-	-	•	•	✓	✓

✓ Standard / • Optional / - HW upgrade required

GNSS Performance	GNSS technology	Leica patented SmartTrack+ technology: • Advanced measurement engine(s) • Jamming resistant measurements • High precision pulse aperture multipath correlator for pseudorange measurements • Excellent low elevation tracking • Minimum acquisition time; Advanced SmartHeading calculation
	Number of channels	120 channels for iCG81, 120 channels per antenna (2x) for iCG82
	Maximum simultaneous tracked satellites	Up to 60 Satellites simultaneously on two frequencies per antenna
	Satellite signals tracking	• GPS: L1, L2, L2C, L5 • GLONASS: L1, L2 • Galileo: E1, E5a, E5b, Alt-BOC • BeiDou B1, B2
	GNSS measurements	Fully independent code and phase measurements of all frequencies: • GPS: carrier phase full wave length, Code (C/A, P, C Code) • GLONASS: carrier phase full wave length, Code (C/A, P narrow Code) • Galileo: carrier phase full wave length, Code • BeiDou: carrier phase full wave length, Code
	Reacquisition time	< 1 sec
Measurement Performance & Accuracy	Accuracy (rms) with real-time (RTK) ¹⁾	
	Standard of compliance	Compliance with ISO17123-8
	Dynamic RTK positioning accuracy, after initialisation	Horizontal: 10 mm + 1 ppm (rms), Vertical: 20 mm + 1 ppm (rms)
	Accuracy (rms) with post processing ¹⁾	
	Static (phase) with long observations	Horizontal: 3 mm + 0.1 ppm (rms), Vertical: 3.5 mm + 0.4 ppm (rms)
	Kinematic (phase)	Horizontal: 10 mm + 1 ppm (rms), Vertical: 20 mm + 1 ppm (rms)
	Heading accuracy (rms) (iCG82 only) ¹⁾	
	Dynamic RTK positioning accuracy, after initialisation	Antenna separation 1 m: < 0.18°, Antenna separation 2 m: < 0.09°, Antenna separation 5 m: < 0.05°
	On-the-fly (OTF) initialisation	
	RTK technology	Leica SmartCheck+ technology
	Reliability of OTF initialisation	Better than 99,99% ¹⁾
	Time for initialisation	Typically 4 sec ²⁾
	OTF range	up to 70 km ²⁾
	Network RTK	
	Network technology	Leica SmartRTK technology
	Supported RTK network solutions	iMAX, VRS, FKP
Supported RTK network standards	MAC (Master Auxiliary Concept) approved by RTCM SC 104	
Hardware	Weight & Dimensions	
	Weight	2'200 g (4.85 lbs) for iCG81, 2'250 g (4.96 lbs) for iCG82
	Dimensions	214.5 mm × 184.8 mm × 85.5 mm (8.44 × 7.27 × 3.36 in) (housing including sockets and mount wings)
	Environmental specifications	
	Operating temperature	-40°C to +65°C (-40°F to +149°F) ³⁾
	Storage temperature	-40°C to +85°C (-40°F to +185°F) ³⁾
	Humidity	100%, compliance with ISO9022-13-06, ISO9022-12-04 and MIL STD 810F - 507.4-I
	Proof against: water, sand and dust	IP67 according IEC60529 and MIL STD 810F - 506.4-I, MIL STD 810F - 510.4-I and MIL STD 810F - 512.4-I Protected against blowing rain and dust; Protected against temporary submersion into water (max. depth 1 m)
	Vibration	5 - 5000 Hz, ± 1.5 mm, 0.7 g; withstands vibrations during operation on large civil construction machines. 5 - 500 Hz, 5 g, ± 15 mm (IEC 60068-2-6) MIL-STD 810G - 514.6E-1-Cat24 MIL-STD 810G - 514.6C-3-Cat4
	Shock	60 g - 6 msec; withstands vibrations during operation on large civil construction machines.
	Drops	Withstands 1.2 m drop onto hard surfaces
	Power & Electrical	
	Supply voltage	Nominal 24 V DC, Range 9 - 36 V DC
	Power consumption	iCG81, NTRIP Rover, radio excluded: 8.0 W typically, 24 V @ 333 mA iCG82, Dual GNSS, NTRIP Rover, radio excluded: 11. W typically, 24 V @ 475 mA
	External power supply	Power can be supplied by 9 V to 36 V DC power supply (machine or vehicle) via a converter cable supplied by Leica Geosystems, via either P1, CAN1 or CAN2. Alternatively by a 110 V - 240 V AC to 12 V DC power supply unit supplied by Leica Geosystems, or rechargeable external NiMH battery 9 Ah / 12 V; with voltage peak protection, Fullfils EN13309
	Certifications	Compliance to: FCC/IC Class B, CE, EN13309, C-Tick, ARIB STD-T66, RoHS, WEEE, ACPEIP

Memory & Data Recording	Memory	
	Internal memory	Built-in memory, 466 MB
	Data capacity	466 MB is typically sufficient for GPS & GLONASS (12+8 satellites) approximately 130 days raw data logging at 15 s rate
	Data recording	
	Type of data	Onboard recording of RINEX data
	Recording rate	Up to 20 Hz
Interface	Buttons	• ON / OFF button • 6 Function buttons (arrow keys – up/down/left/right, Enter, Esc)
	Display	High resolution, 1.8" gray scale display with adjustable backlight: • Provides full receiver status on main screen (position, satellite, radio, modem, battery, Bluetooth®, telematics, memory) • Several submenus for additional details • Various configurations in submenus, e.g. radio channel • Start Base Station with "Here" or type in coordinate • Set up Rover, coordinate system and position output (NMEA or Leica proprietary) • Start and configure raw data logging
	LED status indicator	1 × LED for error status
	Additional functionality	BasePilot functionality (stores up to different 100 base station locations and configurations for quick daily start up without user interaction)
Communication	Communication ports	2 × CAN Power/Data, 1 × serial RS232 Lemo, PWR in, PPS out, 1 × serial RS232 Lemo, 12V PWR out (GFU support) 1 × USB Host, 1 × UART serial & USB (for removable internal RTK devices), 2 × TNC for external GNSS antenna (1 × TNC for iCG81), 1 × TNC for external radio antenna, 1 × TNC for external modem antenna, 1 × M12 Ethernet 1 × Bluetooth® port, Bluetooth® v2.00+ EDR, class 2
	Number of simultaneous data links	Up to 3 real-time output interfaces via independent ports, providing identical or different RTK/RTCM formats
	Built In data links	
	Radio modems	• Optional additional fully integrated, fully sealed receive / transmit radios • User exchangeable device • SATEL M3 TR1: 403 – 470 MHz; up to 1.0 W output power; Pac-crest 4FSK, GMSK & FST, Trimble T & P modulation • Intuicom; 902 – 928 MHz (license free in North America); up to 1.0 W output power
	Radio modem antenna	External antenna connector (Type TNC)
	3G GSM / UMTS / HSPA phone modem	• Built-in phone modem as default • User exchangeable SIM card • Quad-Band UMTS / HSPA: 850 / 900 / 1900 / 2100 MHz • Quad-Band GSM / GPRS: 850 / 900 / 1800 / 1900 MHz • Up to 7.2 mbps downlink speed
	3G GSM / UMTS / HSPA phone modem antenna	External antenna connector (Type TNC)
	External data links	
	Radio modems	• Support of any suitable serial RS232 UHF / VHF radios • Sateline3AS in Leica GFU housing, fully sealed and protected, IP67 • Pacific Crest PDL in Leica GFU housing, fully sealed and protected, IP67 • Sateline TR1, Intuicom 1200DL, TFR-300L in Leica GFU housing, fully sealed and protected, IP67 • Pacific Crest ADL
	Communication protocols	
	Real-time data formats for data transmission	Leica 4G, Leica, CMR, RTCM 3.1, RTCM 3.2 MSM
	Real-time data formats for data reception	Leica 4G, Leica, Leica Lite, CMR, CMR+, RTCM v2.3, RTCM 3.1, RTCM 3.2 MSM
	Web based protocol	NTRIP: receive network corrections; built-in NTRIP Server and Caster to stream local corrections to multiple RTK rovers
	NMEA output	NMEA 0183 V 4.00 and Leica proprietary
	GNSS Antenna	Type
GNSS technology		SmartTrack+
Satellite signals tracking		• GPS: L1, L2, L2C, L5 • GLONASS: L1, L2 • Galileo: E1, E5a, E5b, Alt-BOC • BeiDou B1, B2
Ground plane		Built-in ground plane
Dimensions (diameter × height)		170 mm × 62 mm (6.69 × 2.44 in)
Weight		0.44 kg (0.97 lbs)
Gain		29 dbi
Temperature operating		-40 °C to +70 °C (-40 °F to +158 °F)
Temperature storage		-55 °C to +85 °C (-67 °F to +185 °F)
Humidity		100%
Protection against water, sand		IP66, IP67
Drops & topple over		Withstands 1.5 m drop onto hard surfaces and survives topple over from a 2 m pole onto hard surfaces
Vibration		10 – 10'000 Hz, ± 1.5 mm, 10 g; withstands vibrations during operation on large civil construction machines. 8 – 150 Hz, ± 15 mm, 15 g Compliance with ISO9022-36-08 and MIL-STD 810F – 514.5-Cat24
Shock		100 g, 2 msec; withstands vibrations during operation on large civil construction machines.

¹⁾ Measurement precision and accuracy in position, height and heading are dependent upon various factors including number of satellites, geometry, observation time, ephemeris accuracy, ionospheric conditions, multipath etc. Figures quoted assume normal to favorable conditions. Times required are dependent

upon various factors including number of satellites, geometry, ionospheric conditions, multipath etc. GPS and GLONASS can increase performance and accuracy by up to 30% relative to GPS only. A full Galileo and GPS L5 constellation will further increase measurement performance and accuracy.

²⁾ Might vary due to atmospheric conditions, signal multipath, obstructions, signal geometry and number of tracked signals.
³⁾ Internal Modem operating temperature range is -25°C to +60°C (-13°F to +140°F) and storage temperature range is -30°C to +80°C (-22°F to +176°F)

Highest efficiency and accuracy

For all machine control applications



Maximum performance for all your applications

The iCON gps 80 GNSS machine receiver increases the overall performance of your machine control system and ensures maximum uptime, enabling you to complete different applications faster at uncompromising quality.

Speed up with Leica iCON telematics

iCON telematics is a web-based suite of tools that allow you to increase the efficiency of your machine control operations on site and manage your machinery fleet remotely. The iCON telematics services include fast and easy data transfer from office to site and to construction machines, remote support for the operators and basic fleet management functionality. iCON telematics seamlessly integrates with your workflow on construction projects and the Leica iCON solutions, simplifying work processes and enabling significant time and cost savings.



« Whilst I'm fairly new to the world of machine guidance, I can already see the vast benefits to both safety and production. The new iCON receiver showing a distinct increase in performance and ease of use over the previous model! »

Jim Davis, Machine Operator at Flowline

Leica xRTK for difficult GNSS conditions

Leica xRTK is Leica Geosystems technology that provides additional, reliable positions in difficult measuring environments. It provides highest availability in the most difficult conditions at a slightly lower accuracy than a standard RTK fix.





Leica Geosystems intelligent CONstruction.

Whether you construct buildings, roads, bridges or tunnels, you benefit from intelligent CONstruction. Leica iCON is more than a new product line or software package, it's a complete solution that enables you to enhance your performance and increase your profitability through perfecting your construction workflow.

Understanding construction demands outstanding solutions:

- Custom-built
- Complete
- Straightforward
- High performance

When it has to be right.




The Bluetooth® trade marks are owned by Bluetooth SIG, Inc.

Illustrations, descriptions and technical data are not binding. All rights reserved.
Printed in Switzerland – Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2013.
818196en – 10.14 – galledia



iCONtroll
Brochure



Leica iCON site
Brochure



Leica iCON telematics
Brochure